

Hydrotherapy

# Butterfly Pool

Reviving the Senses

## Rehabilitation & Relaxation Pool

REF. 1243.00

The Butterfly pool offers a playful space of great polyvalence, even in small rooms. Designed to promote rehabilitation and relaxation, it is conceived with an innovative ergonomomy and has been studied to be functional, comfortable and securing.



**REVAL**  
SUSTAINABLE WELL-BEING

# Hydrotherapy



## Rehabilitation & Relaxation Pool

**REF. 1243.00**

### VERSIONS:

REF. 1243.00 Butterfly pool with filtering group, heater, semi automatic chlorination and pH, patient shower head.

### OPTIONS :

- REF. 1243.10 Under water massage system, 6 water/air directional nozzles.
- REF. 1243.20 Air whirlpool with 20 nozzles on the ground of the pool.
- REF. 1243.30 "Kine" lance of massage 0-10 bars.
- REF. 1243.40 Automatic system of injection and self-regulation of the Chlorine and the pH. + Kit of analysis by photometer.
- REF. 1243.60 Chromotherapy option.
- REF. 1243.70 Aromatherapy option (incompatible without the whirlpool option)
- REF. 1243.80 Protecting cover.
- REF. 8905.00 Kit of analysis for Ph and chlorine by photometer.

### MAIN CHARACTERISTICS:

- Tub capacity: 1800 liters.
- Weight of the control panel: 125 kg.
- Weight of the tub without control panel: 200 kg.
- Water volume up to the handrail: 1400 liters.
- Water height up to the handrail: 50cm.
- Pool in white thermoformed acrylic in armed polyester.
- Frame in stainless steel, equipped with 8 adjustable feet for the leveling of the pool.
- Mixer taps Grohe with pouring spout.
- Dosing pumps injecting chlorine and pH.
- Chlorine and pH controls secured with a key.
- 2 tanks of 5L behind a trap door for the chlorine and pH.
- Patient shower head.
- Water meter.
- Skimmer with adjustment valve.
- Drain and suction part with adjustment valve.
- 4 handrails in stainless steel.
- Trap doors secured by key.

### SOUND LEVELS:

- Filtration : 47dBA
- Under water massage system : 57dBA
- Under water massage system + air injection : 61dBA
- Underwater lance of massage : 69dBA
- Air whirlpool : 73dBA

### FILTRATION:

- Regeneration of the water volume (1400 liters) in 24 minutes
- Circulation pump real flow rate : 3.5m<sup>3</sup>/h
- Filter with 3 way valve (filtration, clean, rinse)
- 30kg filtering glass (improved thinness of filtration)
- 3 taps for samples supply point
- Integrated heater 3kw
- Watermeter and manometer of control
- Sensitive control panel with digital thermometer, temperature graduation, clock...

### CONFORMITY:

- Circular n°DGS/EA4/2010/289 dated 27th July 2010 regarding infection's control, especially the prevention of Legionellosis in spas for groups and public spaces.
- Article D1332-1 (sanitary rule for pools)
- EN 1717 (protection against pollution of drinking water in inside networks and main demands of devices against pollution by return)
- 73/23/CEE (directive low voltage)

### UNDERWATER MASSAGE UNIT 6 NOZZLES:

- 6 directional nozzles 15cm height under the water line.
- Massage pump 20m<sup>3</sup>/h
- Control of the air/water mix since the coping of the tub.

### AIR WHIRLPOOL:

- 20 air nozzles on the ground of the tub.
- Blower 1150W with integrated air heater.

### «KINE» LANCE OF MASSAGE UNIT 0-10 BARS:

- 1 lance of massage.
- 1 booster rate 80L/min, pressure 1.5 to 8 bars, adjustable from the control panel.
- 1 pressure manometer 0 to 10 bars

### AROMATHERAPY:

- 1 device diffusing essential oils through the nozzles of the air whirlpool.

